DIGITAL CORE DESIGN

DT8051

Tiny Area 8051-compatible Microcontroller



COMPANY OVERVIEW

Digital Core Design is a leading IP Core provider and a System-on-Chip design house. The company was founded in 1999 and since the very beginning has been focused on IP Core architecture improvements. Our innovative, silicon proven solutions have been employed by over 300 customers and with more than 500 hundred licenses sold to companies like Intel, Siemens, Philips, General Electric, Sony and Toyota. Based on more than 70 different architectures, starting from serial interfaces to advanced microcontrollers and SoCs, we are designing solutions tailored to your needs.

IP CORE OVERVIEW

DT8051 - ULTRA-COMPACT, AREA-OPTIMIZED 8051-COMPATIBLE CPU IP CORE

The **DT8051** is an **area-optimized, ultra-small 8-bit soft microcontroller IP core**, derived from DCD's **industry-proven DP8051 architecture**, the world's fastest and most widely deployed 8051-compatible CPU IP family for over **18 years**.

Designed for **single-chip SoC implementations where silicon area, pin count, and cost are critical**, DT8051 delivers **full 8051 binary compatibility**, excellent performance, and **professional-grade debugging** — all within an **exceptionally low gate count**.

MINIMAL SILICON FOOTPRINT — ONLY ~6,650 GATES

DT8051 features a **very low gate-count architecture**, requiring approximately:

- **6,650 ASIC gates** for the complete system
- Includes **CPU core, peripherals, PMU, and DoCD™ on-chip debugger**

This makes DT8051 one of the **smallest fully featured 8051-compatible CPU IP cores** available, ideal for **cost-sensitive ASICs**, **mixed-signal SoCs**, and **high-volume**

Copyright © 1999 - 2026 DCD - DCD-SEMI Sp. z o.o. All Rights Reserved.
All trademarks mentioned in this document are the property of their respective owners.

consumer devices.

100% 8051 BINARY COMPATIBILITY

DT8051 is **fully binary-compatible with industry-standard 8051 microcontrollers**, enabling:

- Direct reuse of existing firmware and toolchains
- No software porting or recompilation
- Fast migration from discrete MCUs to integrated SoCs

This ensures **zero software risk** while drastically reducing silicon area.

PROVEN PERFORMANCE IN A TINY CORE

Despite its minimal footprint, DT8051 delivers strong performance:

- **Dhrystone 2.1**: **8.1× faster** than the original **80C51** at the same clock frequency
- Benchmarked using the **same C compiler and identical settings**

This performance level is more than sufficient for **control, housekeeping, and peripheral-management tasks**, while keeping power consumption and area to a minimum.

INTEGRATED PERIPHERALS FOR STANDALONE OPERATION

DT8051 includes essential 8051-compatible peripherals, enabling compact standalone SoC designs:

- Timers **0 and 1**
- **Full-duplex UART**
- **Bit-addressable I/O ports**
- **Up to 8 external interrupt sources**
- Interface for **external SFRs**
- **Advanced Power Management Unit (PMU)**

ULTRA-LOW-PIN DEBUGGING WITH TTAG™ (2-WIRE DOCD™)

DT8051 integrates a **2-wire TTAG™ interface**, a compact version of DCD's proprietary **DoCD™ (Digital Core Design on-Chip Debugger)**, specifically designed for **pin-limited applications**.

TTAG™ / DoCD™ Debug Capabilities

- Run, halt, single-step, step-over, instruction skip
- Breakpoints and watchpoints
- Read/write access to:
  - All CPU registers
  - Internal and external program memories
  - All SFRs, including user-defined peripherals
- **Non-intrusive, real-time debugging** of running applications

This provides **professional-grade debug capabilities** without the pin overhead of traditional debug interfaces.

SOC-READY VERIFICATION

DT8051 is delivered with a **fully automated testbench and a complete regression test suite**, enabling:

- Easy IP qualification
- Fast integration into ASIC and FPGA design flows
- Reliable validation at every stage of SoC development

KEY BENEFITS FOR DESIGN ENGINEERS

- **Ultra-small 8051-compatible CPU IP**
- Only **~6,650 ASIC gates** including debug

Copyright © 1999 - 2026 DCD - DCD-SEMI Sp. z o.o. All Rights Reserved.
All trademarks mentioned in this document are the property of their respective owners.

- **8.1× faster** than classic 80C51
- Advanced **PMU for low-power operation**
- Built-in peripherals for compact SoCs
- **2-wire TTAG™ debugger** for pin-limited designs
- Fully synthesizable **ASIC & FPGA-ready soft IP**
- Proven architecture with **18+ years of deployment**

TARGET APPLICATIONS

Cost- & Area-Constrained SoCs

- Mixed-signal ASICs
- Sensor interfaces
- Companion controllers

Low-Power Embedded Systems

- Battery-powered devices
- Always-on housekeeping controllers
- Power-management controllers

Industrial & Consumer

- Simple industrial controllers
- Consumer electronics
- Legacy 8051 system integration

More details about our on-Chip Debugger

Watch the DT8051 presentation on DCD's You Tube:

As Seen On YouTube

ALL DCD'S IP CORES ARE TECHNOLOGY AGNOSTIC, ENSURING 100% COMPATIBILITY WITH ALL FPGA AND ASIC VENDORS.

For further details, email info@dcd-semi.com.

APPLICATIONS

- Low power battery operated devices
- Mixed signal systems
- Area optimized FPGA/ASIC design
- FSM replacements

CPU FEATURES

- Software compatible with the 8051 industry standard
- Very low gate count, area optimized architecture – 6 650 ASIC gates for a **complete system** with DoCD on-chip debugger
- 1 times faster than a standard 8051
- 63 VAX MIPS at 100 MHz
- Up to 256 bytes of internal (on-chip) Data Memory
- Up to 64k bytes of internal (on-chip) Program Memory
- Up to 64k bytes of external (off-chip) Program Memory
- Up to 64k bytes of external (off-chip) Data Memory
- De-multiplexed Address/Data Bus to allow easy connection to memory
- Power Management Unit
  - Power management mode
  - Switchback feature
  - Stop mode
- Interrupt Controller
  - 2 priority levels
  - 8 external interrupt sources
  - 3 interrupt sources from peripherals
- 8-bit I/O Port
  - Bit addressable data direction for each line
  - Read/write of single line and 8-bit group
- Two 16-bit timer/counters
  - Timers clocked by internal source
  - Auto reload 8-bit timers
  - Externally gated event counters
- Full-duplex serial port
  - 8-bit asynchronous mode, variable baud rate
  - 9-bit asynchronous mode, variable baud rate
- Interface for additional Special Function Registers
- **2-wire** DoCD™ debug unit
  - Processor execution control
  - Run, Halt
    - Step into instruction
    - Skip instruction
  - Read-write all processor contents
    - Program Counter (PC)
    - Program Memory
    - Internal (direct) Data Memory
    - Special Function Registers (SFRs)
    - External Data Memory
  - Code execution breakpoints
    - two real-time PC breakpoints
    - unlimited number of real-time OPCODE breakpoints
  - Three independent Memory watchpoints

Copyright © 1999 - 2026 DCD - DCD-SEMI Sp. z o.o. All Rights Reserved.
All trademarks mentioned in this document are the property of their respective owners.

- SFR, DATA, XDATA
- **2-wire** TTAG communication interface

- Fully synthesizable, static synchronous design, with positive edge clocking and no internal tri-states
- Scan test ready

BENEFITS

- Lowest gate count, 8051 compatible architecture
- Very low power consumption
- Significant performance improvement with respect to the 80C51 device, working at the same clock frequency (**1 in terms of Dhrystone MIPS**)
- On demand customization

UNITS SUMMARY

ALU – Arithmetic Logic Unit – performs arithmetic and logic operations during execution of an instruction. Contains accumulator (ACC), Program Status Word (PSW), (B) registers and related logic, like arithmetic unit, logic unit, multiplier and divider.
Control Unit – Performs core synchronization and data flow control. Connected directly to the Opcode Decoder, manages execution of all microcontroller tasks.
Program Memory Interface – Contains Program Counter (PC) and related logic. Performs instructions code fetching. The whole program memory (FLASH or SRAM type) can be written by the DoCD™ debugger or the application can modify some part of its code – for example, storing some data which shouldn't volatile.
External Memory Interface – Contains memory access related registers, like Data Page High (DPH) and Data Page Low (DPL) registers. Performs memory addressing and data transfers.
Internal Data Memory Interface – Controls the access into the internal memory of size up to 256 bytes. Contains 8-bit Stack Pointer (SP) register and related logic.
SFR's Interface – Special Function Register interface manages communication between the CPU and user specified special registers.
Opcode Decoder – Performs an opcode decoding instruction and control functions for all other blocks.
Interrupt Controller – A module responsible for the interrupt manage system for the eight external and internal interrupt sources. Contains interrupt related registers, such as Interrupt Enable (IE), Interrupt Priority (IP), Extended Interrupt Enable (EIE), Extended Interrupt priority (EIP) and (TCON) registers.
Timers – System timers module. Contains two 16bits configurable timers: Timer 0 (TH0, TL0), Timer 1 (TH1, TL1) and Timers Mode (TMOD) registers. In the timer mode, timer registers are incremented every 12 (or 4) CLK periods, when appropriate timer is enabled. In the counter mode, the timer registers are incremented every falling transition on their corresponding input pins (T0, T1), if gates are opened (GATE0, GATE1). T0, T1 input pins are sampled every CLK period. It can be used as clock source for UARTs.
UART – Universal Asynchronous Receiver & Transmitter module is full duplex, meaning, it can transmit and receive concurrently. Includes Serial Configuration register (SCON), serial receiver and transmitter buffer (SBUF) registers. Its receiver is double-buffered so it can commence reception of second byte before the previously received byte has been read from the receive register. Writing to SBUF0 loads the transmit register, and reading SBUF0, reads a physically separate receive register. It works in 2 asynchronous modes with variable baud rate, covering all standard transmission speeds.
Ports – Contains 8051's general purpose I/O ports. Each of port's pins can be read/written as a single bit or as an 8-bit bus.
DoCD™ Debug Unit – **2-wire, low gate count, real-time hardware debugger** which provides debugging capability of a whole SoC system. Unlike other on-chip debuggers, the DoCD™ provides **non-intrusive debugging** of a running application. It can halt, run, step into or skip an instruction, read/write any contents of the microcontroller, including all registers, internal and external program memories and all SFRs, including user defined peripherals. Hardware breakpoints control execution of program memory code; hardware watchpoints can be set and control internal and external data memories and SFRs. Hardware watchpoints are executed if any write/read occurs at particular address, with certain data pattern or without pattern. Two additional pins (CODERUN and DEBUGACS) indicate the state of the debugger and CPU. The CODERUN is active when the CPU is executing an instruction. The DEBUGACS pin is active when any access is performed by the DoCD™ debugger. The DoCD™ system includes **TTAG interface** and complete set of tools, to communicate and work with the core in real time debugging. It is built as a scalable unit and some features can be turned off by the user, to save silicon and reduce power consumption. When the debugger is not used, it is automatically switched to a power save mode. Finally, when the debug option is no longer used, the whole debugger is turned off.

PERFORMANCE

The following tables give a survey about the DT8051 and DoCD on-chip debugger area and performance in **AMD** Programmable Logic Devices (all features included). Results given for a working system with SFR IDATA, CODE and XDATA memories.

Device	Speed grade	Area	F_{max}
SPARTAN-3E	-5	1 029 Slices	75 MHz
VIRTEX-IIP	-7	1 026 Slices	130 MHz
VIRTEX-4	-11	1 031 Slices	140 MHz
VIRTEX-5	-3	579 Slices	200 MHz

DT8051 without the DoCD debugger

Device	Speed grade	Area	F_{max}
SPARTAN-3E	-5	1 172 Slices	75 MHz
VIRTEX-IIP	-7	1 174 Slices	130 MHz
VIRTEX-4	-11	1 177 Slices	140 MHz
VIRTEX-5	-3	625 Slices	200 MHz

DT8051 with a compact version[1] of the DoCD debugger

Copyright © 1999 - 2026 DCD - DCD-SEMI Sp. z o.o. All Rights Reserved.
All trademarks mentioned in this document are the property of their respective owners.

Device	Speed grade	Area	F_{max}
SPARTAN-3E	-5	1 230 Slices	75 MHz
VIRTEX-IIP	-7	1 289 Slices	130 MHz
VIRTEX-4	-11	1 230 Slices	140 MHz
VIRTEX-5	-3	668 Slices	200 MHz

DT8051 with a full version[2] of the DoCD debugger
1- compact DoCD version includes processor execution control (run, halt, reset, step); read-write all processor content (PC, SFRs); read-write all processor memories (IDATA, XDATA, CODE memory); FLASH code memory programming; one hardware code execution breakpoint; unlimited number of OPCODE execution breakpoints
2- full DoCD version includes processor execution control (run, halt, reset, step); read-write all processor content (PC, SFRs); read-write all processor memories (IDATA, XDATA, CODE memory); FLASH CODE memory programming; two hardware code execution breakpoints; six configurable hardware watch-points (IDATA, XDATA, SFRs); unlimited number of OPCODE execution breakpoints

Dhrystone Benchmark Version 2.1 was used to measure the Core performance. The following table gives a survey about the DT8051 performance in Dhrystone/sec and VAX MIPS rating per 1 MHz (DMIPS/MHz).

Device	Dhry/sec [12 MHz]	DMIPS/MHz	80C51 ratio
80C51	197	0,0094	1,00
DT8051	**1 597**	**0,0763**	**8,11**

DELIVERABLES

- HDL Source Code
- Testbench environment
  - Automatic Simulation macros
  - Tests with reference responses
- Synthesis scripts
- Technical documentation
- 12 months of technical support

LICENSING

Comprehensible and clearly defined licensing methods without royalty-per-chip fees make use of our IP Cores easy and simple.
– *Single-Site license option* – dedicated to small and middle sized companies which run their business at one place.
– *Remote Access license option* – allows authorized users to access and use the licensed product from a remote location.
In all cases the number of IP Core instantiations within a project and the number of manufactured chips are unlimited. There are no restrictions regarding the time of use.

The IP is delivered in HDL Source code suitable for ASIC and FPGA projects.

CONTACT

DCD-SEMI Sp. z o.o. Headquarters:
Wroclawska 94, 41-902 Bytom, POLAND
E-mail: info@dcd.pl
tel.: +48 32 282 82 66
fax: +48 32 282 74 37
Distributors:
Please check: dcd.pl/contact-us/

Copyright © 1999 - 2026 DCD - DCD-SEMI Sp. z o.o. All Rights Reserved.
All trademarks mentioned in this document are the property of their respective owners.